

### **AMENDMENTS TO THE CLAIMS**

1-2. (Canceled).

3. (Previously presented) A mobile station receiving method on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, said method comprising:

equalizing and then demodulating said modulated signals from said base station, by using a filter of which frequency characteristics are inverse with that of said radio channels, thereby generating an equalized, demodulated output;  
in parallel, demodulating independently each of said modulated signals and combining the demodulation results, thereby generating a conventional output;  
and  
selecting an output with higher communication quality from the equalized, demodulated output and the conventional output.

4. (Previously presented) The mobile station receiving method according to claim 3, wherein said equalizing step further comprises:  
connecting a plurality of delay circuits in series;  
multiplying a prescribed weight coefficient by the output from each delay circuit using a plurality of multipliers; and  
adding the outputs from said multipliers, wherein said modulated signals are equalized adaptively as the distortions of said radio channels change.

5. (Canceled).

6. (Previously presented) A mobile station receiving apparatus on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, which is characterized in that said mobile station comprises:

a first receiving unit,

a second receiving unit and

a selection unit,

wherein said first receiving unit comprises:

a frequency conversion unit for converting said modulated signals received  
by an antenna into base band signals;

a channel estimation unit for detecting frequency characteristics of said radio  
channels on the basis of said modulated signals;

a filter unit having frequency characteristics that are inverse from said radio  
channels' frequency characteristics; and

a demodulator for demodulating the outputs from said filter unit of which  
inputs are said base band signals, and

said second receiving unit comprises:

a demodulation unit for demodulating independently each of said modulated signals which pass through a plurality of said radio channels of which delay times are different; and  
a combining unit for combining the demodulation results,  
which is characterized in that said selection unit selects an output with higher communication quality among the outputs by said first and second receiving units.

7. (Canceled).

8. (Previously presented) A communication system on a down channel in a CDMA (Code Division Multiple Access) cellular system in which a base station modulates, by using orthogonal pseudo noise sequences, transmission signals towards a plurality of mobile stations, transmits the modulated signals synchronously, while said mobile stations receive the modulated signals distorted by a plurality of radio channels of which delay times are different, said mobile stations comprise:

a first receiving unit, comprising:

- a frequency conversion unit for converting said modulated signals received by an antenna into base band signals;
  - a channel estimation unit for detecting frequency characteristics of said radio channels on the basis of said modulated signals;
  - a filter unit having frequency characteristics which are inverse of frequency characteristics of said radio channels; and
  - a demodulator for demodulating the outputs from said filter unit of which inputs are said base band signals,
- a second receiving unit, comprising:

a demodulation unit for demodulating independently each of said  
modulated signals that pass through said plurality of radio channels,  
where each channel has a different delay time and a combining unit for  
combining the demodulation results, and  
a selection unit that selects an output of said first and second receiving units that  
has higher communication quality.

9. -10. (Canceled).